

M&M Model No.	Capacity	Power Consumption	Motor	R717 Charge	Weight	Dimensions L x W x H	Sound Level	Evaporator				Condenser			
	TR	BHP	HP	lbs	lbs	Feet	dB(A)	No. of Plates	Connections In/Out (inch)	Flow GPM	Pressure Drop (ft)	No. of Plates	Connections In/Out (inch)	Flow GPM	Pressure Drop (ft)
PAC 24-AD	30	26	30	45	5300	6 x 5 x 6.5	67	20	4" / 4"	73	13	28	4" / 4"	86	20
PAC 26-AD	46	39	40	45	5500	6 x 5 x 6.5	68	30	4" / 4"	110	13	42	4" / 4"	130	20
PAC 28-AD	61	52	60	50	5700	6 x 5 x 6.5	70	38	4" / 4"	146	13	54	4" / 4"	173	20
PAC 104S-AD	50	41	50	50	6600	10.5 x 6 x 7	77	32	4" / 4"	120	12	44	4" / 4"	140	20
PAC 104L-AD	63	50	60	50	6600	10.5 x 6 x 7	78	40	4" / 4"	152	12	56	4" / 4"	177	20
PAC 104E-AD	77	60	75	50	6600	10.5 x 6 x 7	78	46	4" / 4"	185	14	68	4" / 4"	217	20
PAC 106S-AD	75	61	75	50	7000	10.5 x 6 x 7	78	46	4" / 4"	180	13	64	4" / 4"	210	21
PAC 106L-AD	95	75	100	55	7000	10.5 x 6 x 7	79	58	4" / 4"	227	13	82	4" / 4"	266	20
PAC 106E-AD	116	90	100	55	7000	10.5 x 6 x 7	79	68	4" / 4"	277	14	98	4" / 4"	326	22
PAC 108S-AD	100	81	125	55	7000	10.5 x 6 x 7	79	60	4" / 4"	239	13	86	4" / 4"	280	21
PAC 108L-AD	127	100	125	55	7000	10.5 x 6 x 7	81	76	4" / 4"	303	14	108	4" / 4"	354	21
PAC 108E-AD	155	120	125	55	7500	10.5 x 6 x 7	80	90	4" / 4"	370	15	130	4" / 4"	434	23
PAC 112S-AD	150	121	200	75	12000	15 x 7 x 7	80	88	4" / 4"	358	15	126	4" / 4"	420	22
PAC 112L-AD	190	150	200	75	12000	15 x 7 x 7	81	110	2 x 4" / 2 x 4"	455	14	158	2 x 4" / 2 x 4"	531	22
PAC 112E-AD	232	179	200	100	12000	15 x 7 x 7	81	134	2 x 4" / 2 x 4"	555	14	196	2 x 4" / 2 x 4"	651	22
PAC 116S-AD	200	162	200	100	13000	15 x 7 x 7	81	116	2 x 4" / 2 x 4"	478	14	168	2 x 4" / 2 x 4"	560	21
PAC 116L-AD	253	200	250	110	13000	15 x 7 x 7	82	146	2 x 4" / 2 x 4"	607	14	210	2 x 4" / 2 x 4"	709	22
PAC 116E-AD	309	239	250	120	13000	15 x 7 x 7	83	178	2 x 4" / 2 x 4"	739	15	258	2 x 4" / 2 x 4"	868	23