

Model	Swept vol. at max. RPM CFM	Bore x Stroke (app. inch)	No. Cylinders	Max. RPM	Capacity Steps %	Rating R717 - 75°/+145°F		Rating R744 - 55°/+20°F		Direct Drive Units		Connections	
						TR	BHP	TR	BHP	Dimensions L x W x H	Weight Without Motor (Lbs)	Suction	Discharge
HPO 24	69	2¾" x 2¾"	4	1800	100-75-50-25	59	51	36	52	56" x 34" x 39"	1100	2"	2"
HPO 26	103	2¾" x 2¾"	6	1800	100-67-50-33	89	79	54	78	56" x 35" x 39"	1190	2½"	2"
HPO 28	137	2¾" x 2¾"	8	1800	100-75-50-25	118	102	72	104	56" x 36" x 39"	1260	2½"	2"
HPC 104S	133	4" x 3¼"	4	1500	100-50	94	79	58	79	87" x 41" x 44"	1875	2½"	2½"
HPC 106S	200	4" x 3¼"	6	1500	100-67-33	140	118	87	119	94" x 43" x 45"	2260	3"	3"
HPC 108S	266	4" x 3¼"	8	1500	100-75-50-25	187	158	116	159	96" x 49" x 45"	2425	4"	3"