

Model	Swept vol. at max. RPM CFM	Bore x Stroke (app. inch)	No. Cylinders	Max. RPM	Capacity Steps %	Rating R717 - 40°/+15°F		Direct Drive Units		V-Belt Drive Units	
						TR	BHP	Dimensions L x W x H	Weight Without Motor (Lbs)	Dimensions L x W x H	Weight Without Motor (Lbs)
TCMO 28	103	2¼" x 2¼"	6LP + 2HP	1800	100-67-50-33	7.1	21	69" x 30" x 32"	1260	66" x 39" x 39"	1420
TSMC 108 S	200	4" x 3¼"	6LP + 2HP	1800	100-67-33	15	43	89" x 40" x 45"	2340	84" x 48" x 44"	2490
TSMC 108 L	250	4" x 4"	6LP + 2HP	1500	100-67-33	20	53	89" x 40" x 45"	2340	84" x 48" x 44"	2490
TSMC 108 E	300	4" x 4¼"	6LP + 2HP	1500	100-67-33	24	68	89" x 40" x 45"	2340	84" x 48" x 44"	2490
TSMC 116 S	399	4" x 3¾"	12LP + 4HP	1800	100-83-67-50-33	30	85	112" x 47" x 52"	4190	84" x 78" x 52"	4590
TSMC 116 L	499	4" x 4"	12LP + 4HP	1500	100-83-67-50-33	39	112	112" x 47" x 52"	4190	84" x 78" x 52"	4590
TSMC 116 E	599	4" x 4¼"	12LP + 4HP	1500	100-83-67-50-33	48	136	112" x 47" x 52"	4190	84" x 78" x 52"	4590
TSMC 188	755	7⅞" x 5½"	6LP + 2HP	1000	100-67-33	61	172	132" x 68" x 66"	8160	124" x 77" x 66"	8450